



**HIGH POWER LED**

**SURFACE MOUNTED LED**

**20W**

**30.000h**  
NOMINAL LIFETIME

**1500 LUMEN**

**6500 KELVIN**

**220-240V~ 50Hz**

**+30cm**  
CONNECTION CABLE

**ALU HOUSING** **IP65** **IN & OUT DOOR**

**AVAILABLE AUGUST 2016**

This 20W LED floodlight can be used indoor and outdoor, for instance at the workshop, jobsite or in the garden, garage or shed. The POWLI20200 with high powered surface mounted LED projects a bright and even floodlight of 1500 lumen with a colour temperature of 6500K.

It has a protection level of IP65 and is therefore dustproof and watertight. On top of that, the aluminium housing makes the floodlight impact-resistant. The POWLI20200 is designed to last up to 30.000 hours. The floodlight can be pointed at different angles thanks to its adjustable bracket.



TECHNICAL SPECIFICATIONS <b>POWLI20200</b>		Features	Box content	Symbols
Power	220-240V~ 50Hz	<ul style="list-style-type: none"> <li>• Surface mounted LED</li> <li>• Adjustable bracket</li> </ul>	1x LED floodlight	<b>CHEMICAL SAFETY</b> ✓ <b>CE</b>
Lumen	1500Lm		1x manual	
Nominal lifetime	30.000h			
Colour temperature	6500K			
Material	Aluminium housing			
Protection degree	IP65			
Connection cable	30cm			
Beam angle	100°			