



**HIGH POWER LED**

**SURFACE MOUNTED LED**

**50W**

**30.000h**  
NOMINAL LIFETIME

**3750 LUMEN**

**6500 KELVIN**

**100-240V~ 50Hz**

**+30cm**  
CONNECTION CABLE

**ALU HOUSING** **IP65** **IN & OUT DOOR**

#### AVAILABLE AUGUST 2016

This LED floodlight can be used indoor and outdoor. Its firm aluminium housing and protection level of IP65 protects it against dust, water and shocks, what makes it perfect for use at the jobsite, in the garden, studio and workshop. It emits 3750 lumen with 50W of electricity which makes it a great energy saving floodlight. The POWLI20500 has a high-quality surface mounted LED light that produces a natural daylight colour temperature of 6500K. The floodlight has a service life of 30.000 operating hours. The floodlight can be pointed at different angles thanks to its adjustable bracket.



TECHNICAL SPECIFICATIONS <b>POWLI20500</b>		Features	Box content	Symbols
Power	100-240V~ 50Hz	<ul style="list-style-type: none"> <li>• Surface mounted LED</li> <li>• Adjustable bracket</li> </ul>	1x LED floodlight	<b>CHEMICAL SAFETY</b> ✓ <b>CE</b>
Lumen	3750Lm		1x manual	
Nominal lifetime	30.000h			
Colour temperature	6500K			
Material	Aluminium housing			
Protection degree	IP65			
Connection cable	30cm			
Beam angle	100°			