



POWLI20501
LED FLOODLIGHT
WITH SENSOR
LED SCHIJNWERPER MET SENSOR
PROJECTEUR À DEL AVEC
DÉTECTEUR
LED STRAHLER MIT SENSOR
FOCO LED CON SENSOR



AVAILABLE AUGUST 2016

This LED floodlight is equipped with a passive infrared sensor that can detect the heat radiation and motion of people, animals or cars within a range of 6 meters. The time delay setting allows you to adjust the light duration from 3 seconds to 5 minutes.

The POWLI20501 with a protection level of IP65 is water-resistant, dustproof and has an impact-resistant housing as the body is built from aluminium. It emits 3750 lumen with 50W of electricity which makes it a great energy saving floodlight.

The floodlight with sensor has a high-quality surface mounted LED light that produces a natural daylight colour temperature of 6500K. It has a service life of 30.000 operating hours and can be pointed at different angles thanks to its adjustable bracket.

HIGH POWER LED

WITH SENSOR

SURFACE MOUNTED LED

50W

30.000h
NOMINAL LIFETIME

3750 LUMEN

6500 KELVIN

220-240V~ 50Hz

+30cm
CONNECTION CABLE

ALU HOUSING **IP65** **IN & OUT DOOR**

TECHNICAL SPECIFICATIONS POWLI20501		Features	Box content	Symbols
Power	220-240V~ 50Hz	<ul style="list-style-type: none"> • Surface mounted LED • Adjustable bracket • Sensor 	1x LED floodlight with sensor	CHEMICAL SAFETY <input checked="" type="checkbox"/> CE
Lumen	3750Lm		1x manual	
Nominal lifetime	30.000h			
Colour temperature	6500K			
Material	Aluminium housing			
Protection degree	IP65			
Connection cable	30cm			
Beam angle	100°			
Sensor range	120°			
Sensor distance	1-6m			
Sensor delay time	3-300sec			
Sensor lux setting	10-1000lux			

