

POWERPLUS
HIGH QUALITY TOOLS



ANTI-KICKBACK

ADJUSTABLE ANGLE

ALLOWS BEVEL CUTS

GUIDE RAIL FOR EXACT CUTTING

4x GUIDE RAIL

2x CLAMP

+ SAW BLADE



POWX0561

PLUNGE SAW 1200W | 165mm

INVALZAAG
SCIE PLONGEANTE
TAUCHSÄGEN
SIERRAS DE INCISIÓN



IMPORTANT FEATURES

1200
WATT

6000
min⁻¹

Ø165
mm

3
YEAR
WARRANTY

1 MODE SELECTOR

FUNCTIEKEUZEKNOP // SÉLECTEUR DE MODE
SCHALTER SÄGEART // SELECTOR DE MODO

2 SCALE FOR CUTTING ANGLE

SCHAAL VAN DE ZAAGHOEK
RÈGLE POUR ANGLE DE COUPE
SCHNITTWINKELSKALA
ESCALA DE ÁNGULO DE CORTE

3 CUTTING DEPTH INDICATORS

INDICATOREN VOOR DE ZAAGDIEPTE
INDICATEURS DE PROFONDEUR DE COUPE
SCHNITTIEFENANZEIGER
INDICADORES DE PROFUNDIDAD DE CORTE

4 SAFETY BUTTON

VEILIGHEIDSKNOP // BOUTON DE SÉCURITÉ
SICHERHEITSTASTE // BOTÓN DE SEGURIDAD

5 ANTI-KICKBACK KNOB

ANTI-TERUGSLAGKNOP // BOUTON ANTI-REBOND
STOPPER GEGEN RÜCKSCHLAG // BOTÓN ANTIRREBOTE

6 DUST CONNECTOR



AANSLUITING VOOR STOFOPVANG
CONNECTEUR DE L'EXTRACTEUR DE POUSSIÈRE
ANSCHLUSS FÜR STAUBABSAUGUNG
CONECTOR DEL EXTRACTOR DE POLVO

7 ADJUSTING KNOB FOR RAIL

INSELKNOP VOOR GELEIDERAIL // BOUTON DE RÉGLAGE DE RAIL
DREHKNOF FÜR SCHIENE // BOTÓN DE AJUSTE DEL CARRIL

8 MAX. CUTTING CAPACITY WITH GUIDE RAILS

MAXIMALE SNIJ/ZAAGCAPACITEIT / CAPACITÉ DE COUPE MAXIMALE
MAX. SCHNEIDLEISTUNG / CAPACIDAD MÁXIMA DE CORTE



POWERPLUS
HIGH QUALITY TOOLS



POWX0561 PLUNGE SAW 1200W

This Powerplus plunge saw is the ideal tool for quick and accurate longitudinal sawing, bevel and plunge cuts. It's intended to cut wood and similar materials, gypsum and cement-bonded fiber materials and plastic. The saw can be slotted into a specifically designed guide rail for perfect, clean sawing anywhere on a panel. This saw cuts through laminates with amazing precision and without any chips at all. Easy to set up. The guide rail segments are joined easily with the connection bars. The mode selector knob allows different modes: change the saw blade, marked cut or plunge cut. To start sawing press and hold the lock button, only then the machine can be safely turned on. Also the anti-kickback knob and fixing clamps ensures solid grip and safe work.

The cutting depth can be set between 0 - 54 mm according to the graduated scale, and the cutting angle can be swiveled between 0° and 48°. Cutting indicators will help you to optimise precision. With the dust extraction adaptor you can connect the plunge saw to a domestic vacuum cleaner. The benefit of the dust extraction is a clear view of the cutting line, a clean working environment and an air without sawdust. The POWX0561 plunge saw is delivered with 4 guide rail segments and 2 clamps. The blade is included.

TECHNICAL SPECIFICATIONS POWX0561		Features	Box content	Symbols
Rated voltage-frequency	230-240V~ 50Hz	<ul style="list-style-type: none"> • Anti-kickback knob • Adjustable angle • Allows bevel cuts • Guide rail for exact cutting • Soft grip • External brush caps for faster carbon brush changes • Dust adaptor for vacuum cleaner incl. 	1x plunge saw	
Rated power	1200W		1x TCT saw blade 24T	
Rotation speed	6000min ⁻¹		1x dust connector	
Max. cutting capacity	with guide rails 54mm (90°) - 38mm (45°)		4x guide rail	
	without guide rails 58mm (90°) - 42mm (45°)		6x bar for connecting guiding rails	
Bevel capacity	0-45°		2x clamp	
Blade dimensions	Ø165x20x2.5mm - 24T		2x hex key	
Cable length	3m		1x manual	

KREATOR ACCESSORIES COMPATIBLE WITH POWX0561			
SAW BLADE 24T	SAW BLADE 48T	SAW BLADE 24T	GUIDE RAIL SEGMENTS
KRT020410 WOOD	KRT020411 WOOD	KRT020304 WOOD	POWX0561X

VARO VARO - VIC. VAN ROMPUY nv - DIY & GARDEN TOOLS
JOSEPH VAN INSTRAAT 9 - 2500 LIER - BELGIUM
TEL +32 (0)3 292.92.92 | FAX +32 (0)3 292.92.72
INFO@VARO.COM | WWW.VARO.COM

Box (piece)



Our +50 years of experience guarantee a professional and high quality service.