

POWERPLUS
HIGH QUALITY TOOLS



INDUCTION MOTOR

CONSTANT HEAT CONTROL

OVERLOAD PROTECTION

3 POSITIONS

+ 4 NOZZLES

+ TRIANGULAR SCRAPER



REFLECTOR NOZZLE:
SOLDERING PIPES



SPREADER NOZZLE:
DRYING, THAWING



REDUCTION NOZZLE:
WELDING, SHRINK SLEEVING



GLASS PROTECTION NOZZLE:
PROTECTING WINDOWS WHEN
STRIPPING FRAMES



STAINLESS STEEL SCRAPER:
STRIPPING PAINT AND VARNISH

POWX1025

HEAT GUN 2000W

HETELUCHTPISTOOL
DÉCAPEUR
HEISSLUFTPISTOLE
DECAPADOR



IMPORTANT FEATURES

2000
WATT

200-500
l/min

**50-
630°C**

3
YEAR
WARRANTY

1 ON/OFF SWITCH // MODE SELECTOR

0: OFF

I: 0-50°C - 200-500 l/min

II: 50-630°C - 200-500 l/min

III: 50-630°C - 500 l/min

AAN-/UITSCHAKELAAR // KEUZESCHAKELAAR

INTERRUPTEUR MARCHE/ARRÊT // COMMUTEUR DE SÉLECTION

EIN-/AUSSCHALTER // FUNKTIONSSCHALTER

INTERRUPTOR DE ENCENDIDO/APAGADO // SELECTOR DE MODO

2 4x NOZZLE + STAINLESS STEEL TRIANGULAR SCRAPER

4x MONDSTUK + ROESTVRIJSTALEN DRIEHOEKIGE SCHRAPER

4x BUSE + GRATTOIR TRIANGULAIRE EN ACIER INOXYDABLE

4x DÜSE + DREIECKIGER SCHABER AUS EDELSTAHL

4x BOQUILLA + RASPADOR TRIANGULAR DE ACERO INOXIDABLE

3 AIR VENTS

VENTILATIESLEUVEN

ORIFICES DE VENTILATION

LÜFTUNGSÖFFNUNGEN

RESPIRADEROS


4 LCD DISPLAY

LCD DISPLAY

ÉCRAN LCD

LCD-ANZEIGE

INDICADOR LCD



1



4

3

POWERPLUS
HIGH QUALITY TOOLS






POWX1025 HEAT GUN 2000W

This heat gun is suitable for drying, thawing, stripping paint, soldering pipes, shrinking PVC or welding plastics. The temperature is adjustable and has a range from 50°C to 630°C. A digital display indicates the exact chosen temperature. The air flow can be changed as well. It starts at 200l/min and at the highest temperature it has a continuous air stream of 500l/min.

To ensure a safe use there is a constant heat control with overload protection. A stainless steel scraper and 4 different nozzles are included. There is a spreader nozzle (to spread the heat), a reduction nozzle (to concentrate the heat), a reflector nozzle (for soldering pipes) and a protection nozzle (to protect glass). The scraper is intended for stripping paint and varnish.



TECHNICAL SPECIFICATIONS POWX1025		Features	Box content	Symbols
Rated voltage - Frequency	230V~ 50Hz	<ul style="list-style-type: none"> • Lightweight • Adjustable air temperature • Constant heat control with overload protection • Digital display with temperature adjust buttons • D-handle 	1x heat gun	  
Rated power	2000W		1x spreader nozzle	
Heat setting I	0-50°C - 200-500 l/min		1x reduction nozzle	
Heat setting II	50-630°C - 200-500 l/min		1x reflector nozzle	
Heat setting III	50-630°C - 500 l/min		1x glass protection nozzle	
Cable length	3m		1x stainless steel scraper	
			1x manual / 1x BMC	

VARO VARO - VIC.VAN ROMPUY nv - DIY & GARDEN TOOLS
JOSEPH VAN INSTRAAAT 9 - 2500 LIER - BELGIUM
TEL +32 (0)3 292.92.92 | FAX +32 (0)3 292.92.72
INFO@VARO.COM | WWW.VARO.COM

Box (piece)



Our +50 years of experience guarantee a professional and high quality service.